DECLARATION OF PERFORMANCE
DS0001

DS

PVC-U Triple Glazed Colour Residential Hinged Door
DS-1.4-NPD-SEP26

ASHI Group Limited
Liberator Road, Norwich, Norfolk, NR6 6EU

BS EN 14351-1:2006+A2:2016
Windows and doors - Product standard, performance characteristics - Part 1: Windows and external pedestrian doorsets without resistance to fire and/or smoke leakage characteristics.

Door intended for use in domestic and commercial locations.

System of AVCP
System 3

Notified Bodies
ERC Testing Ltd (8544) - ISO 10077-1:2017 - Certificate Number: ERC 001

Essential Characteristic	Performance	Classification Standard	Report Reference
Watertightness	NPD	N/A	N/A
Dangerous substances	None	None	Declaration
Resistance to wind load	NPD	N/A	N/A
Load bearing capacity of safety devices	NPD	N/A	N/A
Acoustic performance	NPD	N/A	N/A
Thermal transmittance	≤1.4 W/m^{2}K	ISO 10077-1:2017	ERC 001
Thermal transmittance - windows with single Georgian or cottage bar	≤1.5 W/m^{2}K	ISO 10077-1:2017 EN 14351-1:2006	ERC 001
Thermal transmittance - windows with multiple Georgian or cottage bar	≤1.6 W/m^{2}K	ISO 10077-1:2017 EN 14351-1:2006	ERC 001
Radiation properties	NPD	N/A	N/A
Air permeability	NPD	N/A	N/A

Declaration of Performance

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 [as it has effect in the United Kingdom in respect of Great Britain], under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Matthew Cubitt
Head of Technical & Quality

September 2026
Norwich UK